


## ALGINE 2w1 6W downlight



CE

Power	<b>6 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>750 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>110 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>



See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI037027WW_PW
Power	6 W
Nominal current	48 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	6 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.5
Useful luminous flux*	750 lm (360°)
Luminous flux**	550 lm (360°)
Lamp efficacy	125 lm/W
Luminous intensity	220 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	115x35 mm
Mounting hole	ø95 mm
Weight	0.15 kg
For use	Inside
Assembly method	NATYNK/PODTYNK
Application	Inside
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux