


ALGINE BACKLIGHT 30W led panel 62x62 cm



CE

Power	<b>30 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4200 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>120 °</b>
UGR	<b>&lt;19</b>	Degree of protection (IP)	<b>IP20</b>



See more on dedicated page 



 Declaration of Conformity

Technical data:

Code	SLI035062WW_PW
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4200 lm (360°)
Luminous flux**	3300 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
UGR	<19
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	620x620x32 mm
Weight	2 kg
For use	Inside
Assembly method	NATYNK/PODTYNK
Application	INT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux